

**POLITETRAFLUORETILENE PTFE****BARRE TONDE PIENE ESTRUSE – STAMPATE diametro in mm – peso KG/m**

Lunghezza standard: estruso 1000 o 2000 mm – stampato 300 mm

A richiesta possibili diametri superiori a 200 mm

POLITETRAFLUORETILENE PTFE			POLITETRAFLUORETILENE PTFE			POLITETRAFLUORETILENE PTFE		
Diam.	Tolleranza	Peso appr.	Diam.	Tolleranza	Peso appr.	Diam.	Tolleranza	Peso ap.
6	0/+0,4	0,07	30	0/+1,2	1,65	90	0/+3,6	14,80
7	0/+0,4	0,09	35	0/+1,2	2,25	95	0/+4,0	16,60
8	0/+0,4	0,12	40	0/+1,6	2,90	100	0/+4,0	18,30
10	0/+0,4	0,18	45	0/+2,0	3,72	110	0/+5,0	22,00
12	0/+0,8	0,26	50	0/+2,0	4,60	120	0/+5,0	26,00
14	0/+0,8	0,36	55	0/+2,4	5,55	130	0/+5,0	30,00
15	0/+0,8	0,41	60	0/+2,4	6,60	140	0/+5,0	35,00
16	0/+0,8	0,47	65	0/+2,8	7,75	150	0/+6,0	40,00
18	0/+0,8	0,60	70	0/+2,8	8,90	160	0/+6,0	46,50
20	0/+0,8	0,73	75	0/+3,2	10,30	170	0/+6,0	53,00
22	0/+1,2	0,90	80	0/+3,2	11,80	180	0/+6,0	57,50
25	0/+1,2	1,13	85	0/+3,6	13,20	200	0/+6,0	71,00

NASTRI E LASTRE Spessore e formato in mm – peso Kg/m²

POLITETRAFLUORETILENE PTFE				POLITETRAFLUORETILENE PTFE			
Spessore	Tolleranza	Peso appr.	Formato	Spessore	Tolleranza	Peso appr.	Formato
0,5	0/+0,03	1,14	600/1200/continuo	6	0/+1,0	13,20	600/1200
0,8	0/+0,04	1,82	600/1200/continuo	8	0/+1,2	17,60	600/1200
1	0/+0,1	2,28	600/1200/continuo	10	0/+1,5	22,00	600/1200
1,5	0/+0,1	3,42	600/1200/continuo	12	0/+1,8	26,40	600/1200
2	0/+0,2	4,56	600/1200/continuo	15	0/+2,25	33,00	600/1200
2	0/+0,4	4,56	1500x1500	20	0/+3,0	44,00	600/1200
2,5	0/+0,3	5,70	1500x1500	25	0/+3,75	55,00	600/1200
3	0/+0,3	6,84	600/1200/continuo	30	0/+4,5	66,00	600/1200
3	0/+0,6	6,84	600/1200/1500	40	0/+6,0	88,00	600/1200
4	0/+0,8	8,80	600/1200/1500	50	0/+7,5	110,00	600/1200
5	0/+1,0	11,00	600/1200/1500	60	0/+9,0	132,00	600/1200