

Mozzo in ghisa rivestito in poliuretano per colata "tecnothane"

Cast iron wheel centre coated in cast tecnothane

Основание колеса из чугуна, контактный слой из технотана.

Mozzo con doppio cuscinetto

Hub with two ball bearings

Шариковый подшипник

Disponibili anche con supporti superpesanti elettrosaldati per portate altissime

Available also with electrowelded forks for very high load capacity

Возможны поставки большегрузных стальных сварных кронштейнов



											Codice / Code Наименование модели	
80	25	15	25	35	11	-	-	-	550	-	GT/15S	GT/15C
100	30	15	30	35	11	-	-	-	650	-	GT/16S	GT/16C
125	30	15	35	35	11	-	-	-	1000	-	GT/17S	GT/17C
125	40	20	40	47	14	-	-	-	1000	-	GTL/17S	GTL/17C
150	40	20	40	47	14	-	-	-	1100	-	GT/18S	GT/18C
175	40	20	40	47	14	-	-	-	1100	-	GT/19S	GT/19C
200	50	20	50	52	15	-	-	-	1150	-	GT/20S	GT/20C20
200	50	25	50	52	15	-	-	-	1150	-	GTL/20S	GT/20C
250	50	25	60	52	15	-	-	-	1200	-	GT/21S	GT/21C

ТЯЖЕЛАЯ СЕРИЯ ОЦИНКОВАННЫЕ КРОНШТЕЙНЫ



RUOTA + SGP PESANTE
WHEEL+HEAVY DUTY PLATE SWIVEL BRACKET
ПОВОРОТНЫЙ РОЛИК ПОД ПЛОЩАДКУ

[illegible]

RUOTA + SF PESANTE
WHEEL+HEAVY DUTY FIXED BRACKET
НЕПОВОР. РОЛИК

[illegible]

